

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20600M5W2
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-062-0621
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20600M5W2 Specifications

<b>Fastener Length:</b>	0.254 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Shear Strength:</b>	910 Single Pounds Per Square Inch
<b>Material:</b>	Nickel Alloy 400 Overall
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Any Acceptable Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20600M5W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.