

Description

Fastener Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20600M6W4 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-00-062-0648 |
| Schedule B: | 7508.90.5000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N MS20600M6W4 Specifications

| | |
|--|--|
| Fastener Length: | 0.402 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.186 Inches Minimum And 0.190 Inches Maximum |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.356 Inches Minimum And 0.394 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Shear Strength: | 1440 Single Pounds Per Square Inch |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Overall |
| Surface Treatment: | Any Acceptable Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20600M6W4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.