

Description

Fastener Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20600M6W5
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-062-0649
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	096300, Rivets Brass / Bronze / Copper



* See page 2 for technical characteristics

P/N MS20600M6W5 Specifications

Fastener Length:	0.465 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Shear Strength:	1440 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall
Surface Treatment:	Any Acceptable Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20600M6W5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.