

Description

Fastener Length: 33/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20600M6W6
Minimum Qty (MOQ):	20 EA
NSN:	5320-00-062-0650
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



\* See page 2 for technical characteristics

## P/N MS20600M6W6 Specifications

<b>Fastener Length:</b>	0.527 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Self-plugging
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Shear Strength:</b>	1490 Single Pounds Per Square Inch
<b>Material:</b>	Nickel Alloy 400 Overall
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Any Acceptable Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20600M6W6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.