

**Description**

Fastener Length: 29/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS20600MP6W5                                |
| Minimum Qty (MOQ):      | 25 EA                                       |
| NSN:                    | 5320-00-062-0670                            |
| Schedule B:             | 7508.90.5000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20600MP6W5 Specifications

|   |   |
|---|---|
| <b>Fastener Length:</b>                               | 0.465 Inches Maximum  |
| <b>Head Style:</b>                                    | Universal   |
| <b>Head Height:</b>                                   | 0.080 Inches Minimum And 0.090 Inches Maximum                 |
| <b>Shank Diameter:</b>                                | 0.186 Inches Minimum And 0.190 Inches Maximum                 |
| <b>Shank Style:</b>                                   | Self-plugging   |
| <b>Head Major Diameter:</b>                           | 0.356 Inches Minimum And 0.394 Inches Maximum                 |
| <b>Expansion Device:</b>                              | Serrated Stem-type W  |
| <b>Grip Length:</b>                                   | 0.251 Inches Minimum And 0.312 Inches Maximum                 |
| <b>Shear Strength:</b>                                | 1440 Single Pounds Per Square Inch                            |
| <b>Material:</b>                                      | Nickel Alloy 400 Overall                                      |
| <b>Material Document And Classification:</b>          | Qq-n-281 Fed Spec Single Material Response Overall            |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20600MP6W5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.