

Description

Fastener Length: 3/8", MS20601 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CR9162-4-04

SKU / Model:

MS20601AD4W4

Minimum Qty (MOQ):

100

NSN:

5320-00-582-3502

Schedule B:

7616.10.3000

ECCN:

EAR99

National Motor Freight:

013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20601AD4W4 Specifications

Fastener Length:	0.357 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Special Features:	W/special Pulling Head
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Nondefinitive Spec/std Data:	2 Type And 2 Class

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20601AD4W4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.