

Description

Fastener Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20601AD4W8
Minimum Qty (MOQ):	50 EA
NSN:	5320-00-835-5368
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N MS20601AD4W8 Specifications

Fastener Length:	0.607 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy 2117 Sleeve
Material:	Aluminum Alloy 2017 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Chromate Stem
Surface Treatment:	Anodize Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Fed Spec 3rd Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-c-5541 Fed Spec 3rd Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20601AD4W8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.