

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20601AD5W10 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-008-2446 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20601AD5W10 Specifications

| | |
|---|--|
| Fastener Length: | 0.754 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.155 Inches Minimum And 0.159 Inches Maximum |
| Shank Style: | Self-plugging |
| Head Major Diameter: | 0.286 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.563 Inches Minimum And 0.625 Inches Maximum |
| Shear Strength: | 580 Single Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |
| Nondefinitive Spec/std Data: | 2 Type And 2 Class |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20601AD5W10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.