

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20601AD5W12
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-164-0811
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20601AD5W12 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.688 Inches Minimum And 0.750 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Color Sleeve Orange
Material:	Aluminum Alloy 2117 Sleeve Or Aluminum Alloy 5056 Sleeve
Material:	Aluminum Alloy 2017 Stem Or Aluminum Alloy 5056 Stem
Material Document And Classification:	Qq-a-430 Fed Spec All Material Responses Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec All Material Responses Stem
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment:	Anodize Stem Or Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Stem Or Mil-c-5541 Mil Spec 2nd Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20601AD5W12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.