

Description

Fastener Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20601MP4W8
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-181-6220
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20601MP4W8 Specifications

Fastener Length:	0.587 Inches Minimum And 0.607 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy Stem
Material:	Nickel Alloy Sleeve
Surface Treatment:	Cadmium Sleeve
Surface Treatment:	Cadmium Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20601MP4W8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.