

Description

Fastener Length: 1/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20604AD3C1
Minimum Qty (MOQ):	20
NSN:	5320-00-181-6866
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N MS20604AD3C1 Specifications

Fastener Length:	0.140 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Expansion Device:	Mandrel-type C
Grip Length:	0.015 Inches Minimum And 0.062 Inches Maximum
Shear Strength:	70 Single Pounds Per Square Inch
Material:	Aluminum Alloy 2117 Sleeve
Material:	Aluminum Alloy 2117 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Chromate Sleeve
Surface Treatment:	Chromate Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Stem
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604AD3C1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.