

Description

Fastener Length: 1/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20604AD3C1 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5320-00-181-6866 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS20604AD3C1 Specifications

| | |
|---|---|
| Fastener Length: | 0.140 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Shank Diameter: | 0.093 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Pull Through Hollow Shank |
| Head Major Diameter: | 0.178 Inches Minimum And 0.196 Inches Maximum |
| Expansion Device: | Mandrel-type C |
| Grip Length: | 0.015 Inches Minimum And 0.062 Inches Maximum |
| Shear Strength: | 70 Single Pounds Per Square Inch |
| Material: | Aluminum Alloy 2117 Sleeve |
| Material: | Aluminum Alloy 2117 Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Stem |
| Surface Treatment: | Chromate Sleeve |
| Surface Treatment: | Chromate Stem |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec 1st Treatment Response Stem |
| Surface Treatment Document And Classification: | Mil-c-5541 Mil Spec 1st Treatment Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604AD3C1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.