

Description

Fastener Length: 13/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20604AD3C2
Minimum Qty (MOQ):	10
NSN:	5320-00-987-1223
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20604AD3C2 Specifications

Fastener Length:	0.203 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Expansion Device:	Mandrel-type C
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Shear Strength:	70 Single Pounds Per Square Inch
Material:	Aluminum Alloy 2117 Sleeve
Material:	Aluminum Alloy 2117 Mandrel
Material Document And Classification:	Qq-a-430 Assn Std Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Assn Std Single Material Response Mandrel
Surface Treatment:	Anodize Mandrel
Surface Treatment:	Anodize Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Mandrel
Surface Treatment Document And Classification:	Mil-s-8625 Mil Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604AD3C2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.