

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20604AD3C3
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-530-0840
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20604AD3C3 Specifications

Fastener Length:	0.265 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Expansion Device:	Mandrel-type C
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Body
Material:	Aluminum Alloy 2117 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Body
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Body Or Chromate Body
Surface Treatment:	Anodize Stem Or Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Body Or Mil-s-5541 Mil Spec 2nd Treatment Response Body
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Stem And Mil-s-5541 Mil Spec 2nd Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604AD3C3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.