

**Description**

Fastener Length: 5/32

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR9117-4-01](#)

SKU / Model:

MS20604AD4W1

Minimum Qty (MOQ):

100

NSN:

5320-00-074-4594

Schedule B:

7616.10.3000

ECCN:

EAR99

National Motor Freight:

013630, Alum Rivets

NO IMAGE  
AVAILABLE

## P/N MS20604AD4W1 Specifications

<b>Fastener Length:</b>	0.170 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.124 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.015 Inches Minimum And 0.062 Inches Maximum
<b>Shear Strength:</b>	125 Single Pounds Per Square Inch
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Mil-w-7986 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Oxide Film Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604AD4W1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.