

Description

Fastener Length: 17/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20604AD4W7
Minimum Qty (MOQ):	25 EA
NSN:	5320-00-963-4037
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	061680, Elec Wiring Plugs Etc



\* See page 2 for technical characteristics

# P/N MS20604AD4W7 Specifications

Fastener Length:	0.544 Inches Nominal
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Knob Stem-type K
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604AD4W7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.