



Military-Fasteners.com

P/N MS20604AD6W4

Description

Fastener Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20604AD6W4
Minimum Qty (MOQ):	20 EA
NSN:	5320-00-957-2507
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20604AD6W4 Specifications

Fastener Length:	0.426 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	275 Single Pounds Per Square Inch
Material:	Aluminum Alloy 2117 Sleeve
Material:	Aluminum Alloy 2117 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment:	Anodize Stem Or Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Stem Or Mil-c-5541 Mil Spec 2nd Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604AD6W4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.