

Description

Cherry Pull-thru Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20604H3W2
Minimum Qty (MOQ):	50 EA
NSN:	5320-01-374-1841
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N MS20604H3W2 Specifications

Head Style:	Universal
Head Height:	0.178 Inches Minimum And 0.196 Inches Maximum
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.040 Inches Minimum And 0.050 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.125 Inches Nominal
Material:	Iron Alloy 660 Sleeve Steel Comp 305 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve ASTM A493 Comp 305 Assn Std Single Material Response Stem
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve Passivate Stem
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Fed Spec All Treatment Responses Sleeve Qq-p-35 Fed Spec All Treatment Responses Stem

How to Order

Order this cherry pull-thru rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604H3W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.