

P/N MS20604H3W2

Description

Cherry Pull-thru Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS20604H3W2

Minimum Qty (MOQ): 50 EA

NSN: 5320-01-374-1841

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



^{*} See page 2 for technical characteristics

P/N MS20604H3W2 Specifications

Head Style:	Universal
Head Height:	0.178 Inches Minimum And 0.196 Inches Maximum
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.040 Inches Minimum And 0.050 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.125 Inches Nominal
Material:	Iron Alloy 660 Sleevesteel Comp 305 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeveastm A493 Comp 305 Assn Std Single Material Response Stem
Surface Treatment:	Cadmium Sleeve And Chromate Sleevepassivate Stem
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Fed Spec All Treatment Responses Sleeveqq-p-35 Fed Spec All Treatment Responses Stem

How to Order

Order this cherry pull-thru rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/MS20604H3W2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.