

Description

MS20604H3W3 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20604H3W3
Minimum Qty (MOQ):	25
NSN:	5320-01-287-2965
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in all caps.

NO IMAGE
AVAILABLE

P/N MS20604H3W3 Specifications

Fastener Length:	0.265 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Material:	Steel Comp 305 Stem
Material Document And Classification:	Astm A493 Assn Std Single Material Response Stem
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604H3W3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.