

**Description**

MS20604H3W3 Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20604H3W3
Minimum Qty (MOQ):	25
NSN:	5320-01-287-2965
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N MS20604H3W3 Specifications

<b>Fastener Length:</b>	0.265 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.040 Inches Minimum And 0.050 Inches Maximum
<b>Shank Diameter:</b>	0.092 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.178 Inches Minimum And 0.196 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.126 Inches Minimum And 0.187 Inches Maximum
<b>Material:</b>	Steel Comp 305 Stem
<b>Material Document And Classification:</b>	Astm A493 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604H3W3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.