

Description

Cherry Pull-thru Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS20604H3W4 |
| Minimum Qty (MOQ): | 40 EA |
| NSN: | 5320-01-396-6985 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20604H3W4 Specifications

| | |
|---|--|
| Fastener Length: | 0.328 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Shank Diameter: | 0.092 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.178 Inches Minimum And 0.196 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| End Item Identification: | Pacer Dawn |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Steel Comp 305 Stem |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Sleeve |
| Material Document And Classification: | Astma493 Assn Std Single Material Response Stem |
| Surface Treatment: | Cadmium Sleeve |
| Surface Treatment: | Passivate Stem |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Stem |
| Surface Treatment Document And Classification: | Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Sleeve |

How to Order

Order this cherry pull-thru rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604H3W4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.