

Description

Cherry Pull-thru Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20604H3W4
Minimum Qty (MOQ):	40 EA
NSN:	5320-01-396-6985
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20604H3W4 Specifications

Fastener Length:	0.328 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Pacer Dawn
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Steel Comp 305 Stem
Material Document And Classification:	Ams5731 Assn Std Single Material Response Sleeve
Material Document And Classification:	Astma493 Assn Std Single Material Response Stem
Surface Treatment:	Cadmium Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this cherry pull-thru rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604H3W4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.