

Description

Fastener Length: 9/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20604M4W3
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-062-7887
Schedule B:	8308.90.9000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N MS20604M4W3 Specifications

Fastener Length:	0.295 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.123 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Shear Strength:	185 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall
Surface Treatment:	Any Acceptable Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604M4W3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.