



Military-Fasteners.com

P/N MS20604ML3W4

Description

Fastener Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20604ML3W4
Minimum Qty (MOQ):	20 EA
NSN:	5320-01-011-3142
Schedule B:	8308.90.9000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N MS20604ML3W4 Specifications

Fastener Length:	0.328 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Material:	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
Material:	Nickel Alloy 400 Stem Or Nickel Alloy R-405 Stem
Material Document And Classification:	Qq-n-281 Cl A Fed Spec All Material Responses Sleeve
Material Document And Classification:	Qq-n-281 Cl A Fed Spec All Material Responses Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604ML3W4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.