

Description

Fastener Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20604ML4W2
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-066-3561
Schedule B:	8308.90.9000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20604ML4W2 Specifications

Fastener Length:	0.232 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.123 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Material:	Nickel Alloy 400 Sleeve
Material:	Steel Stem
Material Document And Classification:	Astm A-545 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-n-281,cl A Fed Spec Single Material Response Sleeve
Precious Material:	Silver
Surface Treatment:	Silver Sleeve
Surface Treatment:	Silver Stem
Surface Treatment Document And Classification:	Qq-s-365 Assn Std Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-s-365 Assn Std Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604ML4W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.