

Description

Fastener Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | MS20604ML4W2 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-01-066-3561 |
| Schedule B: | 8308.90.9000 |
| ECCN: | 9A991 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20604ML4W2 Specifications

| | |
|---|--|
| Fastener Length: | 0.232 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.123 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Pull Through Hollow Shank |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.063 Inches Minimum And 0.125 Inches Maximum |
| Material: | Nickel Alloy 400 Sleeve |
| Material: | Steel Stem |
| Material Document And Classification: | Astm A-545 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-n-281,cl A Fed Spec Single Material Response Sleeve |
| Precious Material: | Silver |
| Surface Treatment: | Silver Sleeve |
| Surface Treatment: | Silver Stem |
| Surface Treatment Document And Classification: | Qq-s-365 Assn Std Single Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-s-365 Assn Std Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604ML4W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.