

**Description**

Fastener Length: 7/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20604ML4W2
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-066-3561
Schedule B:	8308.90.9000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20604ML4W2 Specifications

<b>Fastener Length:</b>	0.232 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.123 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Material:</b>	Nickel Alloy 400 Sleeve
<b>Material:</b>	Steel Stem
<b>Material Document And Classification:</b>	Astm A-545 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-n-281,cl A Fed Spec Single Material Response Sleeve
<b>Precious Material:</b>	Silver
<b>Surface Treatment:</b>	Silver Sleeve
<b>Surface Treatment:</b>	Silver Stem
<b>Surface Treatment Document And Classification:</b>	Qq-s-365 Assn Std Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-s-365 Assn Std Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604ML4W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.