

## Description

pull-thru rivet, MS20604 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS20604R3W3
Minimum Qty (MOQ):	100
NSN:	5320-01-359-2322
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N MS20604R3W3 Specifications

<b>Fastener Length:</b>	0.265 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.0400 Inches Minimum And 0.0500 Inches Maximum
<b>Shank Diameter:</b>	0.0920 Inches Minimum And 0.0970 Inches Maximum
<b>Head Major Diameter:</b>	0.1780 Inches Minimum And 0.1960 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.1260 Inches Minimum And 0.2500 Inches Maximum
<b>Material:</b>	Iron Alloy 660 Sleeve Steel Comp 305 Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Sleeve A-493 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Passivate Sleeve Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Sleeve Qq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604R3W3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.