

Description

Fastener Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20604R3W4
Minimum Qty (MOQ):	75 EA
NSN:	5320-01-377-3708
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in all caps.

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20604R3W4 Specifications

Fastener Length:	0.328 Inches Nominal
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Shear Strength:	105 Single Pounds Per Square Inch
Special Features:	Dry Film Lube Per Mil-I-46010, Type 1
Material:	Iron Alloy 660 Sleeve
Material:	Steel Comp 305 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve
Material Document And Classification:	Astm-a-493 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	96906-ms20604h Government Specification

How to Order

Order this cherry pull-thru rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604R3W4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.