

**Description**

Cherry Pull-thru Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CCR274CS-4-02](#)

SKU / Model:	MS20604R4W2
Minimum Qty (MOQ):	40
NSN:	5320-01-359-4667
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20604R4W2 Specifications

<b>Fastener Length:</b>	0.232 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.0540 Inches Minimum And 0.0640 Inches Maximum
<b>Shank Diameter:</b>	0.1230 Inches Minimum And 0.1280 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.2380 Inches Minimum And 0.2620 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.0620 Inches Minimum And 0.1250 Inches Maximum
<b>Material:</b>	Iron Alloy 660 Sleeve Steel Comp 305 Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Sleeve A-493 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Passivate Sleeve Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Sleeve Qq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this cherry pull-thru rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604R4W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.