

Description

Cherry Pull-thru Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CCR274CS-4-02](#)

SKU / Model:	MS20604R4W2
Minimum Qty (MOQ):	40
NSN:	5320-01-359-4667
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20604R4W2 Specifications

Fastener Length:	0.232 Inches Maximum
Head Style:	Universal
Head Height:	0.0540 Inches Minimum And 0.0640 Inches Maximum
Shank Diameter:	0.1230 Inches Minimum And 0.1280 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.2380 Inches Minimum And 0.2620 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.0620 Inches Minimum And 0.1250 Inches Maximum
Material:	Iron Alloy 660 Sleeve Steel Comp 305 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve A-493 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Sleeve Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Sleeve Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this cherry pull-thru rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604R4W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.