

**Description**

Cherry Pull-thru Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20604R5W2
Minimum Qty (MOQ):	25 EA
NSN:	5320-01-354-2548
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N MS20604R5W2 Specifications

<b>Head Style:</b>	Tapered Pan
<b>Head Height:</b>	0.0670 Inches Minimum And 0.0770 Inches Maximum
<b>Shank Diameter:</b>	0.1540 Inches Minimum And 0.1590 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.2960 Inches Minimum And 0.3280 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.0630 Nominal Mils And 0.1250 Nominal Centimeters
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Steel Comp 305 Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Sleeve
<b>Material Document And Classification:</b>	Astm A493 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Passivate Sleeve
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this cherry pull-thru rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604R5W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.