

Description

Cherry Pull-thru Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20604R5W5
Minimum Qty (MOQ):	50 EA
NSN:	5320-01-339-1478
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20604R5W5 Specifications

Fastener Length:	0.441 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.154 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Steel Comp 305 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve
Material Document And Classification:	Astm A493 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this cherry pull-thru rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604R5W5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.