

Description

MS20604 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20604S3W2
Minimum Qty (MOQ):	100
NSN:	5320-01-251-9285
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS20604S3W2 Specifications

Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Nominal Mils And 0.125 Nominal Centimeters
Material:	Steel Comp 1008 Sleeve Or Steel Comp 1012 Sleeve Or Steel Comp 1018 Sleeve
Material:	Steel Comp 1008 Stem
Material Document And Classification:	Astm A545 Assn Std Single Material Response Sleeve
Material Document And Classification:	Astm A545 Assn Std Single Material Response Stem
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604S3W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.