

## Description

MS20604 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS20604S3W2
Minimum Qty (MOQ):	100
NSN:	5320-01-251-9285
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS20604S3W2 Specifications

<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.040 Inches Minimum And 0.050 Inches Maximum
<b>Shank Diameter:</b>	0.092 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Self-plugging High Clinch Shank
<b>Head Major Diameter:</b>	0.178 Inches Minimum And 0.196 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.063 Nominal Mils And 0.125 Nominal Centimeters
<b>Material:</b>	Steel Comp 1008 Sleeve Or Steel Comp 1012 Sleeve Or Steel Comp 1018 Sleeve
<b>Material:</b>	Steel Comp 1008 Stem
<b>Material Document And Classification:</b>	Astm A545 Assn Std Single Material Response Sleeve
<b>Material Document And Classification:</b>	Astm A545 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604S3W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.