

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20604S3W3
Minimum Qty (MOQ):	75 EA
NSN:	5320-01-547-7284
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N MS20604S3W3 Specifications

Fastener Length:	0.265 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Part Name Assigned By Controlling Agency:	Rivet,blind,nonstructural,universal Head,class 1
Special Features:	Serrated Stem Is Used
Material:	Steel Comp 1008 Overall
Material Document And Classification:	Astm A510 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Sae Ams-qq-p-416b Assn Std Single Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604S3W3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.