

Description

Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20604S3W5
Minimum Qty (MOQ):	55 EA
NSN:	5320-01-497-8329
Schedule B:	7318.23.0000
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N MS20604S3W5 Specifications

Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
End Item Identification:	Kc-130j Ae2100d3 Engine-contractor Suppt.; Engine Model Code Ae2100d3 For Kc-13j
Grip Length:	0.250 Inches Minimum And 0.312 Inches Maximum
Criticality Code Justification:	Agav
Material:	Steel Comp 1008 Overall Or Steel Comp 1012 Overall Or Steel Comp 1118 Overall
Material Document And Classification:	Astm A510 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Type Ii, Class 2 Fed Spec Single Treatment Response Overall

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604S3W5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.