

## P/N MS20604S4W3

### **Description**

Blind Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS20604S4W3

Minimum Qty (MOQ): 30 EA

NSN: 5320-01-453-4912

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20604S4W3 Specifications

Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Maximum
Material:	Steel Comp 1008 Overall Or Steel Comp 1012 Overall Or Steel Comp 1018 Overall

# **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/MS20604S4W3">https://military-fasteners.com/rivets/blind+rivets/MS20604S4W3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/MS20604S4W3">https://military-fasteners.com/rivets/blind+rivets/MS20604S4W3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/MS20604S4W3">https://military-fasteners.com/rivets/blind+rivets/MS20604S4W3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/ms20604S4W3">https://military-fasteners.com/rivets/ms20604S4W3</a> and selecting the quantity you want then