

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20604S4W5
Minimum Qty (MOQ):	25
NSN:	5320-01-497-8366
Schedule B:	7318.23.0000
ECCN:	EAR99



P/N MS20604S4W5 Specifications

Head Style:	Small Pan
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.123 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Kc-130j Ae2100d3 Engine-contractor Suppt.; Engine Model Code Ae2100d3 For Kc-13j
Grip Length:	0.248 Inches Minimum And 0.310 Inches Maximum
Criticality Code Justification:	Agav
Material:	Steel Comp 1008 Stem
Material:	Steel Comp 1018 Sleeve Or Steel Comp 1008 Sleeve Or Steel Comp 1012 Sleeve
Material Document And Classification:	Astm A510 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty II, Class 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205 - Nas-20604 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604S4W5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.