

### Description

Blind Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

### Additional Information

SKU / Model:	MS20604S4W5
Minimum Qty (MOQ):	25
NSN:	5320-01-497-8366
Schedule B:	7318.23.0000
ECCN:	EAR99



## P/N MS20604S4W5 Specifications

<b>Head Style:</b>	Small Pan
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.123 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging High Clinch Shank
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>End Item Identification:</b>	Kc-130j Ae2100d3 Engine-contractor Suppt.; Engine Model Code Ae2100d3 For Kc-13j
<b>Grip Length:</b>	0.248 Inches Minimum And 0.310 Inches Maximum
<b>Criticality Code Justification:</b>	Agav
<b>Material:</b>	Steel Comp 1008 Stem
<b>Material:</b>	Steel Comp 1018 Sleeve Or Steel Comp 1008 Sleeve Or Steel Comp 1012 Sleeve
<b>Material Document And Classification:</b>	Astm A510 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Ty II, Class 2 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205 - Nas-20604 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20604S4W5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.