



★ FASTENERS

Military-Fasteners.com

P/N MS20605AD3C4

Description

Fastener Length: 5/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20605AD3C4
Minimum Qty (MOQ):	25
NSN:	5320-00-068-8302
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20605AD3C4 Specifications

Fastener Length:	0.328 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.179 Inches Nominal
Expansion Device:	Mandrel-type C
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 2117 Sleeve
Material:	Aluminum Alloy 2117 Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Stem
Surface Treatment:	Anodize Sleeve Or Chromate Sleeve
Surface Treatment:	Anodize Stem Or Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Stem Or Mil-c-5541 Mil Spec 2nd Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605AD3C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.