

**Description**

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20605AD3C5
Minimum Qty (MOQ):	50 EA
NSN:	5320-01-380-0129
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20605AD3C5 Specifications

<b>Fastener Length:</b>	0.390 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.179 Inches Nominal
<b>Expansion Device:</b>	Mandrel-type C
<b>Grip Length:</b>	0.251 Inches Minimum And 0.312 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 2117 Sleeve
<b>Material:</b>	Aluminum Alloy 2117 Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Stem
<b>Surface Treatment:</b>	Anodize Sleeve Or Chromate Sleeve
<b>Surface Treatment:</b>	Anodize Stem Or Chromate Stem
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Stem Or Mil-c-5541 Mil Spec 2nd Treatment Response Stem

## How to Order

Order this rivet blind from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605AD3C5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.