

Description

Fastener Length: 7/16", serrated stem, steel stem, MS20605 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20605AD3W6
Minimum Qty (MOQ):	100
NSN:	5320-01-510-1167
Schedule B:	7616.10.3000
ECCN:	EAR99



P/N MS20605AD3W6 Specifications

Fastener Length:	0.453 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.094 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Drive Pin
Head Major Diameter:	0.179 Inches Nominal
Expansion Device:	Serrated Stem-type W
End Item Identification:	Acft, Orion P-3
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 2117 Sleeve
Material:	Steel Stem
Material Document And Classification:	Astma510 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Specification/standard Data:	80205-nas-20605 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605AD3W6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.