

**Description**

Fastener Length: 7/16", serrated stem, steel stem, MS20605 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20605AD3W6
Minimum Qty (MOQ):	100
NSN:	5320-01-510-1167
Schedule B:	7616.10.3000
ECCN:	EAR99



## P/N MS20605AD3W6 Specifications

<b>Fastener Length:</b>	0.453 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.094 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Drive Pin
<b>Head Major Diameter:</b>	0.179 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>End Item Identification:</b>	Acft, Orion P-3
<b>Grip Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Aluminum Alloy 2117 Sleeve
<b>Material:</b>	Steel Stem
<b>Material Document And Classification:</b>	Astma510 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Sleeve
<b>Specification/standard Data:</b>	80205-nas-20605 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605AD3W6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.