

Description

Fastener Length: 15/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20605AD4W6
Minimum Qty (MOQ):	50
NSN:	5320-00-957-1410
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS20605AD4W6 Specifications

Fastener Length:	0.482 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.225 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Shear Strength:	125 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 2117 Sleeve
Material:	Aluminum Alloy 2117 Stem
Material Document And Classification:	Mil-w-7986 Mil Spec Single Material Response Sleeve
Material Document And Classification:	Mil-w-7986 Mil Spec Single Material Response Stem
Surface Treatment:	Anodize Sleeve And Chromate Sleeve
Surface Treatment:	Anodize Stem And Chromate Stem
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Sleeve Or Mil-c-5541 Mil Spec 2nd Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Stem Or Mil-c-5541 Mil Spec 2nd Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605AD4W6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.