

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20605AD5W6
Minimum Qty (MOQ):	30 EA
NSN:	5320-00-957-1425
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N MS20605AD5W6 Specifications

Fastener Length:	0.524 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Head Major Diameter:	0.286 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.251 Inches Minimum And 0.375 Inches Maximum
Shear Strength:	190 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Mil-w-7986 Mil Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605AD5W6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.