

Description

Fastener Length: 1/4",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20605B3W3
Minimum Qty (MOQ):	25
NSN:	5320-00-838-7851
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N MS20605B3W3 Specifications

Fastener Length:	0.265 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.179 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Shear Strength:	70 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Aluminum Alloy 5056 Stem
Material Document And Classification:	Mil-w-7986 Mil Spec Single Material Response Sleeve
Material Document And Classification:	Mil-w-7986 Mil Spec Single Material Response Stem
Surface Treatment:	Chromate Stem
Surface Treatment:	Anodize Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605B3W3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.