

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS20605B5W2 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-01-509-3437 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20605B5W2 Specifications

| | |
|---|--|
| Fastener Length: | 0.274 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.154 Inches Minimum And 0.159 Inches Maximum |
| Shank Style: | Pull Through Hollow Shank |
| Head Major Diameter: | 0.282 Inches Minimum And 0.290 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Aluminum Alloy 5056 Sleeve |
| Material: | Steel Stem |
| Material Document And Classification: | Astm A-510 Assn Std Single Material Response Stem |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Sleeve |
| Surface Treatment: | Anodize Sleeve |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Sleeve |
| Specification/standard Data: | 80205-nas-20605 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605B5W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.