

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20605B5W2
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-509-3437
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20605B5W2 Specifications

Fastener Length:	0.274 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.154 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.282 Inches Minimum And 0.290 Inches Maximum
Expansion Device:	Serrated Stem-type W
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Sleeve
Material:	Steel Stem
Material Document And Classification:	Astm A-510 Assn Std Single Material Response Stem
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Sleeve
Surface Treatment:	Anodize Sleeve
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Sleeve
Specification/standard Data:	80205-nas-20605 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605B5W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.